



Utsifting Oslo S Del 3



Eksisterende		Pos	Type	Info	Ant	Erstatning	Art.nr	Betegnelse	Info
		1	Innf downl 1x70W HIT	175mm hull i metallhimling	52			RS750B LED27S/840 PSED-E MB SI CU5	Leveres med dekkring RAL 9006, DALI
		2	Innf downl 2x18W	20 cm hull i metallhimling. IP44. Grå	14			DN571B LED20S/840 PSED-E C PG CU5 GR	Leveres med IP54 glass, DALI
		3	Innf downl 2x32W	25 cm hull i metallhimling. Grå	43			DN571B LED40S/840 PSED-E C CU5 GR	Leveres med dekkring RAL 9006, DALI
		4	Utenpål rund armatur 2x26W	Ø350mm. Grå. IP44?	9			WL120V LED16S/840 PSR GR	Leveres i grå, Ø344mm, ELV dim
		5	Innf downl 2x26W	20 cm hull i metallhimling. IP44? Grå	19			DN571B LED24S/840 PSED-E C PG CU5 GR	Leveres med IP54 glass, DALI
		6	Innf downl 2x26W	20 cm hull. IP44. Grå	41			DN571B LED24S/840 PSED-E GR IP54	Leveres med IP54 glass, DALI
							Trykk på link for å komme til produktet på nett		